



# DCN-CON Concentus Basic



The DCN-CON is the standard delegate conference unit that enables delegates to speak, register a request-to-speak, register a response request, listen to the speaker and vote. It has low susceptibility to interference from mobile phones. A socket is provided to connect the pluggable microphones (DCN-MICS and DCN-MICL, to be ordered separately). The flat-panel loudspeaker offers superior acoustics with minimal feedback, thus increasing intelligibility. It is automatically muted when the microphone is activated. When the unit is not being used, the loudspeaker panel conveniently folds down. There are five voting buttons for all kind of voting. An external contact is available to connect external fingerprint readers.

- ▶ **Low susceptibility to mobile phones**
- ▶ **Compact, attractive delegate unit**
- ▶ **Built-in fold-away flat-panel loudspeaker**
- ▶ **Five voting buttons**
- ▶ **Cable connections located underneath the unit**
- ▶ **External present and fraud contact**

- PRESENT, YES (+), NO (-), ABSTAIN (X), (parliamentary voting)
- Numerals: 1 to 5 (multiple choice or opinion polls)
- Rating scale: - -, -, 0, +, ++ (audience response)

#### Connections

- Socket for pluggable microphone
- 2 m (78.7 in) cable terminated in a molded six-pole circular connector
- Six-pole circular connector for loop-through connections
- Eight-pole modular jack connector for Intercom Handset LBB 3555/00 and external present and Fraud contact e.g. a fingerprint reader

## Functions

### Controls and indicators

- Built-in, fold-away, flat-panel loudspeaker, automatically muted if the microphone is on
- Microphone 'on/off' or 'request-to-speak' button
- 'Microphone on' indicator at the top of the loudspeaker
- Tri-color indicator above the microphone button:
  - Red 'Microphone on' indicator
  - Green 'Request-to-speak' confirmation indicator
  - Yellow 'VIP' indicator. 'VIP' LED is lit when the delegate unit is part of the notebook, which is only available when PC control software is used
- Five voting buttons with yellow LED confirmation indicators These can be used to register:

## Certifications and Approvals

Region	Certification
Europe	CE

**Technical Specifications**

**Mechanical**

Mounting	Tabletop (portable or fixed mounting) and flush mounting
Dimensions (H x W x D)	<b>(without microphone)</b>
Tabletop	50 x 275 x 155 mm (2.0 x 10.8 x 6.1 in)
Flush mounted	30 x 275 x 155 mm (1.2 x 10.8 x 6.1 in)
Weight	1.4 kg (3.1 lb)
Color top	Charcoal (PH 10736) with silver (RAL 9022) panel
Color base	Charcoal (PH 10736)

**Ordering Information**

<b>DCN-CON Concentus Basic</b> pluggable microphone, voting, microphone to be ordered separately	<b>DCN-CON</b>
---	----------------

**Accessories**

<b>DCN-MICL Pluggable Long Microphone</b> length 480 mm (18.9 inch), silver	<b>DCN-MICL</b>
<b>DCN-MICS Pluggable Short Microphone</b> length 310 mm (12.2 inch), silver	<b>DCN-MICS</b>

**Americas:**  
Bosch Communications Systems  
12000 Portland Avenue South  
Burnsville, Minnesota, 55337, USA  
Phone: +1-800-392-3497  
Fax: +1-800-955-6831  
audiosupport@us.bosch.com  
www.boschcommunications.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Bosch Security Systems Pte Ltd  
38C Jalan Pemimpin  
Singapore 577180  
Phone: +65 6319 3450  
Fax: +65 6319 3499  
apr.securitysystems@bosch.com  
www.boschsecurity.com

**Represented by**