



DCN-FVU-CN Voting Unit Chinese



- ▶ IF design award
- ▶ Colored voting buttons
- ▶ Chinese text
- ▶ LED unit active indicator
- ▶ Stylish design, which fits both modern and traditional meeting rooms
- ▶ Direct loop through connection to the DCN network
- ▶ LED vote confirmation indicators
- ▶ Allows parliamentary voting
- ▶ Economic solution for positions that only require voting facilities.

The unit is used for attendance registration, parliamentary voting and for/against voting. It is provided with colored voting buttons and Chinese text. The texts are: present, yes, no and abstain and the colors are respectively: white, green, red and yellow. The yellow LED confirmation indicators are used to prompt the user to indicate presence and to vote and to confirm registration of what is voted. The blue LED unit active indicator shows that the system is in normal operation. The blue LED flashes when the unit detects a communication fault.

The combination of the voting unit with the end caps forms a very stylish design, which fits in both modern and traditional meeting rooms. The direct connection to the DCN network cable is an economic solution for positions that only require voting facilities.

Functions

Controls and Indicators

- Four voting buttons with yellow confirmation indicators to register: present, yes, no and abstain
- One unit active indicator. The blue LED indicates that the system is in normal operation. The blue LED flashes when the unit detects a communication fault.
- One de-init/init button (rear side of the unit)

Interconnections

- 1 m (39.4 in) DCN cable terminated with a molded six-pole male circular connector
- 1 m (39.4 in) DCN cable terminated with a molded six-pole female circular connector for loop-through connection to the DCN network

Note An unused output cable must be terminated by a DCN-CBTRP Termination Plug.

Technical Specifications

Mechanical

| | |
|-------------------------------|--|
| Mounting | Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with DCN-FCOUP couplings and DCN-FEC end caps in any surrounding |
| Dimensions (H x W x D) | 40 x 100 x 82 mm |
| Weight | 250 g |
| Color | Silver (RAL 9022) |

Ordering Information

Model | Description

DCN-FVU-CN Voting Unit Chinese
direct loop-through connection to DCN network, flush mounted, silver

Americas:
Bosch Security Systems
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 585 223 4060
Fax: +1 800 289 0096
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 (0) 40 27 83955
Fax: +31 (0) 40 27 86668
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by