



DCN-DISD Basic Discussion Unit



- ▶ Low susceptibility to mobile phone interference
- ▶ Compact, attractive and ergonomic design
- ▶ Pluggable microphone
- ▶ Built-in loudspeaker
- ▶ Headphone output level reduction to prevent acoustic feedback (active when listening to the floor and when the microphone is on) *
- ▶ Usable as delegate unit, dual delegate unit, chairman unit or single delegate unit with auxiliary button

The Basic Discussion Unit enables participants to speak, register a request-to-speak and listen to the speaker. A socket is provided to connect the pluggable microphones (DCN-MICS and DCN-MICL, to be ordered separately).

The unit also accommodates two separate headphone connections with individual volume control on either side of the unit, allowing one unit to serve two delegates. It can be converted to a full dual-use unit by replacing the microphone button with two separated microphone buttons for individual microphone control and individual delegate identification (DCN-DISBDD dual-use buttons, to be ordered separately).

The built-in loudspeaker speaker is muted when the microphone is on to prevent acoustic feedback. Different rims are available to allow matching with the interior (DCN-DISR, to be ordered separately). The unit can be used as a single delegate unit, as a dual delegate unit, as a chairman unit (DCN-DISBCM chairman buttons, to be ordered separately) or as a single delegate unit with auxiliary button. The versatile auxiliary button can be used as an usher call, for example.

To lock the loop-through cable, a cable clamp is available (DCN-DISCLM, to be ordered separately).

The unit is available in light- and dark-colored bases.

Functions

Controls and Indicators

- Microphone button with a red, green or yellow illuminated ring. Red indicates microphone is active, green indicates request-to-speak accepted, and yellow indicates 'VIP'. *
- VIP indicator is lit when the delegate is part of the notebook (only available if PC Software is used)
- Two individual headphone volume control buttons
- Recessed 'De-init' switch

Interconnections

- Socket for pluggable microphone
- Two 3.5 mm headphone sockets (0.14 in) stereo jack type
- 2 m (78.7 in) cable terminated within a molded six-pole circular connector.
- Six-pole circular connector for loop-through connections

* When unit is used in Dual Delegate mode, this function is available individually.

Technical Specifications

Electrical

Frequency response	30 Hz - 20 kHz
Headphone load impedance	> 32 ohm < 1k ohm
Output power	2 x 15 mW/32 ohm

Mechanical

Mounting	Tabletop (portable or fixed mounting) and flush mounting
Dimensions (H x W x D)	(without microphone)
Tabletop	61 x 190 x 116 mm (2.4 x 7.5 x 4.6 in)
Flush mounted	6 x 190 x 120 mm (0.2 x 7.5 x 4.7 in)
Weight	800 g (1.76 lb)
Color top	Silver (RAL 9022)
Color base	
DCN-DISD-L	Light Grey (RAL 000 7500)
DCN-DISD-D	Charcoal (PH 10736)

Ordering Information

Model | Description

DCN-DISD-L Basic Discussion Unit pluggable microphone, light base
DCN-DISD-D Basic Discussion Unit pluggable microphone, dark base

Hardware Accessories

DCN-MICS Pluggable Microphone Short stem length 310 mm (12.2 inch)
DCN-MICL Pluggable Microphone Short stem length 480 mm (18.9 inch)
DCN-DISRH-SR Rims for Discussion Units silver, high gloss, set of 10
DCN-DISR-SR Rims for Discussion Units silver, set of 10
DCN-DISR-D Rims for Discussion Units dark, set of 10
DCN-DISRMH Rims for Discussion Units metal, high gloss, set of 10
DCN-DISRMS Rims for Discussion Units metal, semi gloss, set of 10
DCN-DISBCM Buttons for Chairman Discussion Unit set of 10
DCN-DISBDD Buttons for Dual Use Discussion Unit set of 10
DCN-DISCLM Cable clamps for Discussion Unit set of 25
DCN-FCDIS Flight Case for Discussion Units holds 10 discussion units with microphones

Americas:
Bosch Security Systems
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 585 223 4060
Fax: +1 800 289 0096
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 (0) 40 27 83955
Fax: +31 (0) 40 27 86668
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by